

磁気平衡式／電流出力型

Servo system Current-output type

S20S M1 SERIES

RoHS指令
適合品

仕様 SPECIFICATIONS

Ta=+25°C, Vcc= ±15V

| 項目 Spec | カタログ品番 Types | | | |
|---|--------------|---|---------|---------------------------------|
| | S20S200D15M1 | | | |
| 定格電流 Primary nominal current | If | 200AT | | 300AT |
| 測定抵抗 Measuring resistance | RL | Vcc=±12V | 5Ω~35Ω | Vcc=±12V |
| | | Vcc=±15V | 25Ω~65Ω | Vcc=±15V |
| 定格出力電流 Rated output current | Io | 100mA(巻線比 Turn Ratio: 1 : 2000) | | 150mA(巻線比 Turn Ratio: 1 : 2000) |
| 出力電流精度 Output current accuracy | XG | Io±1% (without lof) | | |
| オフセット電流※1 Offset current | lof | ≤ ±0.5mA (at If=0A) | | |
| 最大電流@Vcc±15VDC&Ta=70°C Maximum current | Ifmax | ±300AT (at RL=30Ω) | | |
| 出力直線性 Output linearity | εL | ≤ ±0.25% (at If) | | |
| 電源電圧 Power supply voltage | Vcc | ±12V±5%~±15V±5% (Rated output current is restricted by Vcc) | | |
| 消費電流 Consumption current | Icc | ≤ ±16mA (without Io) | | |
| di/dt 応答速度 Response time | tr | ≤ 1μs (di / dt = If/μs) | | |
| 周波数特性@-1dB Frequency characteristics | f | DC~150kHz | | |
| 出力電流温度係数 Thermal drift of gain | Tclo | ≤ ±0.02%/°C (Without Tc lof) (-5°C~+70°C) | | |
| オフセット電流温度係数 Thermal drift of offset | Tclof | ≤ ±0.012mA/°C (-5°C~+70°C) | | |
| ヒステリシス誤差 Hysteresis error | IoH | ≤ 0.3mA (at If = 0A → If → 0A) | | |
| 絶縁耐圧 Insulation voltage | Vd | AC2500V、1分間(感応電流 0.5mA)、貫通部内側 ⇌ 端子一括間 AC2500V for 1 minute (Sensing current 0.5mA) inside of through hole ⇌ terminal | | |
| 絶縁抵抗 Insulation resistance | Ris | ≥ 500MΩ (at DC500V) 貫通部内側 ⇌ 端子一括間 inside of through hole ⇌ terminal | | |
| 動作温度範囲 Ambient Operating temperature | Ta | -20°C~+70°C | | |
| 保存温度範囲 Ambient storage temperature | Ts | -20°C~+85°C | | |
| 2次側コイル抵抗値 Secondary coil resistance | Rs | 33Ω @ Ta=70°C | | |

※1 オフセット電流はコアヒステリシス除去後の値とする。 *1 Offset current value is after removal of core hysteresis.

外形図 DIMENSIONS (mm)

